





110-Ton, 4 Axle, Detachable Gooseneck, Non-Ground Bearing, **Beam Trailer**

General: This Specification is for Model GTBN1104-55-24-HGG, 110-Ton, 4 Axle, Detachable Gooseneck, Non-

Ground Bearing, Beam Trailer, Max Payload is 220,000 lbs.

Dimension: (All dimensions are nominal and are subject to change)

· Overall Length: 659" (16.738M)

· Overall Width: 102" (2.590M)

· Gooseneck: 155" (3.937M)

· Swing Clearance: 110" & 86" (2.794M & 2.184M)

· Load well Length: 288" (7.315M)

· Rear Deck: 168" (4.267M)

· Flip Axle Length: 48" (1.219M)

· 5th Wheel Height: 50" (1.270M)

· King Pin Setting: 16" & 40" (.406M & 1.016M)

· Ground Clearance: 8" (.203M)

· Deck Height: 28" (.711M)

Frame:

· Main Beam: Fabricated T-1 "I" beam, 100,000 PSI.

· Cross Member: "I" beams on 12" Centers

· Rear Tail: Fabricated T-1 "I" beam, 100,000 PSI.

Axles: 4 - 30,000 lbs capacity axles, 3rd axle lift, 4th flip.

King Pin: 2", two position removable heavy duty.

Wheels & Tires: - Tires: 16 ea 315/80R x 22.5, steel belted radials.

- Wheels: 16 ea. 8.25 x 22.5, 10 hole hub piloted steel disc wheels.

Brakes: 16.5 x 7 full air brakes with spring parking brakes, automatic slack adjusters 4S2M ABS.

Suspension: Cush air ride 30K yoke mount suspension, 3rd axle air lift, with auto dump valve, & +/-

3 air ride adjustment with weight gauge.

Rear Tail Section: Open wheel, boom & bucket well, set up for 4th axle flip.





















Electrical: 12-Volt electrical system, 7 way SAE connector, all lighting LED mounted in rubber

grommets to DOT

standards.

Hydraulics: Pony motor & wet line hook-up for tractor PTO operation.

Tie Downs: 20 ea "D" Ring tie downs 8 ea side on main deck, 2 on rear deck, chain slots in

bolsters.

Finish: Sandblasted to near white primed and powder coated fluorescent green.















